



MANUFACTURER IMPORTER & SUPPLIER OF CONSTRUCTION MACHINERY







Authorised Dealer





Our Subsidiary

MIRAI CONSTECH

SMIIT CONSTECH









INDEX

TIVIT REBAR PROCESSING MACHINE	
➤ INDIAN BAR BENDING & CUTTING MACHINES	1
➤ DECOILING & FULLY AUTOMATIC STIRRUP MACHINES	2
➤ IMPORTED BAR BENDING & CUTTING MACHINES	3
➤ OTHER REBAR PROCESSING MACHINES & SPARES	4
• SOIL COMPACTORS	
➤ RAMMERS, PLATE COMPACTORS, ROLLERS, ETC	5
• LIFTS & HOIST	
➤ MATERIAL HOIST, PM HOIST, SUSPENDED ROPE PLATFORM,	
MONKEY HOISTS, TOWER CRANE BUCKETS, ETC	5
• CONCRETE TOOLS	
➤ CONCRETE VIBRATORS, NEEDLES, CONCRETE PUMP, MIXERS	7
• ANTI SMOG GUN	
➤ ANTI POLLUTION MACHINE	7
• FLOORING MACHINES & TOOLS	
➤ VDF, FLOATER, GROOVE CUTTER BULL FLOAT,	
TEXTURE BRUSH, ETC	8
WACKER NEUSON EQUIPMENT	
➤ HMS, IREN & IRFU HIGH FREQUENCY VIBRATORS	9
➤ SHUTTER VIBRATORS & FREQUENCY CONVERTORS	0
➤ RAMMERS, WALK BEHIND ROLLER & PLATE COMPACTORS 1	1

TMT REBAR PROCESSING MACHINE





Planetary Gearbox



MODEL NO.	SM TW42	SM TW45 (42 PRO)	SM TW52	SMTW55
CAPACITY	Upto 32 mm Ø	Upto 32 mm Ø	Upto 36 mm Ø	Upto 40 mm Ø
DISC SIZE	320 mm	350 mm	390 mm	480mm
BUSH SUPPLIED (OD) Can be customised upto	55, 70 & 90 mm Upto 110 mm	55, 70 & 90, 120 mm Upto 135 mm	55, 70, 90 & 120 mm Upto 160 mm	55, 70, 90, 120, 160 & 220 mm Upto 260 mm
BUSH Ø as per IS Code (≈)*	4D of 25 mm 3D of 32 mm	5D of 25 mm 4D of 32 mm	6D of 25 mm 5D of 32 mm	7D of 32 mm 6D of 40 mm
MOTOR POWER	5 HP, 415 V, 1440 RPM	5 HP, 415 V, 1440 RPM	7.5 HP, 415 V, 1440 RPM	7.5 HP, 415 V, 1440 RPM
DISC ROTATION RPM	9	9	9	6
MACHINE SIZE (LxBxH) inch	24 x 32 x 35	26 x 34 x 37	28 x 36 x 39	30 x 39 x 43
GEAR BOX TYPE & BRAND	Top Gear Transmission - Planetary (Zero Maintenance) & 1.5 Year Replacement Guarantee			
PANEL BRAND	ABB Contactors, With GIC make VPR System, Giovenzana make Padel, Telemechanique Limit Switches & Teknik make socket. PLC (Optional for added safety)			
WEIGHT (Kgs.)	315 kgs	330 kgs	350 kgs	620 kgs

OIL / GREASE FREE GEARBOX, ZERO MAINTENANCE MACHINE, SILENT, MAXIMUM SAFETY, CUSTOMIZED AS PER CIVIL ENGINEERING I.S. CODES. 100% ALL PARTS PROUDLY MADE IN INDIA. RUGGED AND HARDEST MATERIAL USED IN DISC, SADDLES & PIN BUSH.

CAN BE CUSTOMIZED FOR 8D USAGE AND SPECIALLY FOR U BOLT & J BOLTS MANUFACTURING.

BAR CUTTING MACHINE (INDIAN SERIES)

Single & Two Stage Gearbox



MODEL	SBC 42	SBC 52	SBC 55
CAPACITY	Upto 32 mm Ø	Upto 36 mm Ø	Upto 40 mm Ø
BLADE TYPE	RECTANGLE (4 SIDES USABLE)		
MOTOR POWER	5 HP, 415 V, 2880 RPM	5 HP, 415 V, 2880 RPM	7.5 HP, 415 V, 2880 RPM
GEAR BOX	Single Stage	Two Stage	Two Stage
STROKES / MIN	42 Strokes	39 Strokes	34 Strokes
STARTER BRAND & TYPE	PANEL TYPE STARTER - our own customised		
BLADE SIZE (MM)	78x58x24	85x58x28	85x55x32
WEIGHT (Kgs.)	450	520	620



PANEL TYPE STARTER WITH VPR, SPP & VOLTAGE INDICATOR, WITH 5 PIN POWER SOCKET. NO OIL DRIPPING FROM BLADE MOTOR & STARTER PROPERLY COVERED FROM WATER, FAST STROKES OF CUTTING & ROBUST MACHINE.

BAR CUTTING MACHINE PREMIUM HYBRID SERIES



MODEL	SM - GQ40	SM - GQ42D	SM - GQ50
TMT CAPACITY	6 TO 32 mm Ø	6 TO 36 mm Ø	6 TO 40 mm Ø
MOTOR POWER	5 HP, 2800 RPM, 415 V (Indian)	5 HP, 2800 RPM, 415 V (Indian)	7.5 HP, 2800 RPM, 415 V (Indian)
BLADE TYPE	SQUARE (All 8 Sides Usable)		
GEARBOX TYPE	3 Stage Type	2 Stage Type	3 Stage Type
STARTER BRAND & TYPE	Siemens Make - DOL Starter		
BLADE	28 Strokes	30 Strokes	25 Strokes
WEIGHT	420 Kgs.	510 Kgs.	550 Kgs.
SIZE OF MACHINE (LxBxH) Inch	51 x 21 x 27	42 x 20 x 35	54 x 22 x 28

Indian Brand ISI make motor, Havells/Siemens DOL Starter, Oil should Dripping from Blade Indian Copper Winding Motor.

TMT BAR DECOILING MACHINE

MODEL	GTQ 6-14	GTQ 6-10
TMT COIL CAPACITY	6 TO 12 mm Ø	6 TO 8 mm Ø
MOTOR POWER	16.5 kW	7.5 kW
STRAIGHTENING SPEED	40- 50 mtr/min	34- 40 mtr/min
PRE STRAIGHTENING WHEELS	8 wheels	N/A
CUTTING SPACE	900 mm	900 mm
WEIGHT	1180 Kgs.	550 Kgs.



TMT Coils Straightening & Cutting Machine with & without Payoff, with panel. Heavy Duty & Sturdy Machine.

FULLY AUTOMATIC CNC STIRRUP RING MAKING MACHINE

MODEL	SMIT D4	SMIT D2
CAPACITY (TMT COIL)	6 TO 12 mm TMT COIL (550D)	6 TO 10 mm TMT COIL (550D)
SINGLE WIRE DOUBLE WIRE	12 mm 6 TO 10 mm	10 mm 6 TO 8 mm
SPEED	2800 Rings/hr*	2000 Rings/hr*
SPECIALITY	Large Infra Projects	Stirrups Resellers
DIRECTION	Bi Directional	Single Directional
MOTOR CAP.	38.75 kW	15.5 kW
PAY OFF	2-2.5 Tonne (Air Brake type)	1-1.5 Tonne (Regular type)
WEIGHT	3500 Kgs.	2500 Kgs.



BAR BENDING MACHINES (IMPORTED SERIES)



MODEL	GW42 A (Heavy)	GW42 J (Eco)	GW50
CAPACITY	Up to 32 mm Ø	Up to 32 mm Ø	Upto 40 mm Ø
MOTOR POWER	5 HP, 415 V, 1440 RPM	5 HP, 415 V, 1440 RPM	5 HP, 415 V, 1440 RPM
DISC RPM	10-12 RPM	10-12 RPM	8-10 RPM
BEND WHEEL DIA	360 mm	360 mm	400 mm
WEIGHT (Kgs.)	350	325	450

BRAKE MOTOR AND BELT SYSTEM

Simple Panel of 2 Contactor System. With Break Motor. Oil/Grease required. Belt type gearbox Machine.

BAR CUTTING MACHINE (IMPORTED SERIES)

MODEL	GQ40	GQ50	
TMT CAPACITY	6 TO 32 mm Ø	6 TO 40 mm Ø	
MOTOR POWER	5 HP, 2880 RPM, 415 V	7.5 HP, 2880 RPM, 415 V	
POWER ON / OFF	MCB / DOL Starter		
GEARBOX	3 Stage Heli	cal Gearbox	
STROKES OF CUTTING	28 Times/min	34 Times/min	
BLADE	Square Blade all 8 Sides Usable		
WEIGHT (Kgs.)	400	515	



IMPORTED motor, Indian Starter, Oil should keep Dripping from Blade. IMPORTED copper winding motor.

STIRRUP RING MAKING MACHINES (90° & 135°)



MODEL	GF20 LIMIT	GF20 DIGITAL
CAPACITY	Heavy - 16 mm Eco - 12 mm	Heavy - 16 mm Eco - 12 mm
MOTOR	3 PH - 1 PH - 220V	
PADELS	2 NOS	2 NOS.
WEIGHT	Heavy - 115 Kgs. Eco - 98 Kgs.	Heavy - 115 Kgs. Eco- 98 Kgs.



SPIRAL TMT RING MACHINE (FOR PIERS & PILES)



MODEL	OWH-32	OWH-25
TMT CAPACITY	16 TO 32 MM Ø	16 TO 25 MM Ø
MOTOR POWER	5 HP, 1440 RPM, 415 V	5 HP, 1440 RPM, 415 V
BENDING SPEED	12 RPM	12 RPM
WEIGHT	330 Kgs.	280 Kgs.
MINI. BENDING DIA.	Ø 200 mm	Ø 250 mm

TMT SCRAP BAR STRAIGHTENING MACHINE



MODEL	GX 6-12	GX 16-25	GX 10-25
TMT DIA	6 TO 12 MM Ø	16 TO 25 MM Ø	10 TO 25 MM Ø
CUTTER	Attached	N/A	upto 12 mm
MOTOR POWER	5 HP + 2.5 HP	10 HP	22 HP
WEIGHT	750 Kgs.	950 Kgs.	1150 Kgs.


TMT BAR COLD FORGING & THREADING MACHINE



TMT Cold Forging Machine to upset TMT Bar before Threading Up to 40 mm TMT Bar Capacity

TMT Bar Thread Chasing Machine (Latthe type) Up to 40 mm TMT Bar





TMT Bar Thread Rolling Machine

upto 40 mm TMT Bar 16-20 - 2.0 mm pitch 25-32 - 2.5 mm pitch 36-40 - 3.0 mm pitch Limit / Sensor Type Eco / Heavy Model

SPARE PARTS

All types of Pin Bush Sets For Bar Bending Machine



All kinds of Limit Switches



All Types of Foot Padels & Sockets



Blades for Cutting Machines All Models & All Makes



Threading M/c Rollers, Chasers, & Blades



Rebar Jointing Couplers





Imported Rammer with Honda Petrol Engine / Electric Motor



Walk Behind Double Drum Roller with 10 HP Diesel Greaves Make Engine Self Start + Hour Meter & Engine Guard & Water Tank FOR SOIL COMPACTION ONLY



Single Drum Roller with Petrol/ Diesel Engine



Imported Forward Plate Compactor with Honda Engine 2-2.5 kN (Tonne)



Imported Reversible Compactor with Greaves Diesel Engine 4-5 kN (tonne)



Indian Forward Compactor 4-5 kN - Diesel / Electric



Indian Plate Compactor Mini - For paver block 1.5 - 2.0 kN




XCMG WB Roller with 8.5 HP Changfa (Chineese) / or 10 HP Greaves Diesel Engine FOR SOIL COMPACTION ONLY



Ride on Double Drum Roller for Soil Compaction

LIFTS & HOISTS



Material Hoist
1.0 & 1.5 Tonne Capacity - upto 175 mtr. Height


Traditional H-Frame Type
Tower Hoist



Men & Material Hoist

1, 1.5 & 2 Tonne Capacity
Single & Twin Cage.
upto 175 mtr. Height

Monkey Hoist / JIB Crane 250, 350 & 500 Kgs. Capacity upto 75 mtr. Height



CONCRETE TOOLS




Handy High Speed Concrete Vibrator 1000 Watt / 2000 Watt / 2500 Watt



Electric Motor Type Concrete Vibrator 1 HP, 2 HP & 3 HP | 1 or 3 Phase



Mini Concrete Pump Electric / Diesel Throw upto 150 mtr



All Types of Needles 35 mm, 40 mm, 45 mm, 50 mm & 65 mm 1.5 mtr to 6 mtrs length



Hand Held Surface Concrete Vibrator




Mini Concrete Mixers 180, 220, 300, 360 Ltrs Capacity

ANTI POLLUTION



Anti Smog Gun
Electric
Trolley / Truck Mounted
Throw upto 35 mtrs
Water Tank - 1000 to 1500 ltrs.
Tilting Angle- 12 - 55 Degree
Horiz. Rotation - 350 Degree

FLOORING MACHINES & TOOLS





Road Groove Cutter Indian & Imported Electric, Diesel & Petrol - upto 9" Depth Cutting





Screed Vibrators
Truss Screed | WB Screed | Double Beam Screed


Concrete Finisher

WACKER NEUSON EQUIPMENTS

CONCRETE VIBRATORS

1. HMS VIBRATOR (MECHANICAL CHAIN TYPE)

HEAD + MOTOR + SHAFT



MODEL	MOTOR	SHAFT	HEAD Ø
HMS SET 525	M 2500 (2.5 HP)	SM5S (5 mtr Long)	H55 (55 mm Ø).
HMS SET 425	M2500	SM5S	H 45
HMS SET 325	M2500	SM5S	H 35
OTHER VARIANT		SM4E (4 mtr Long)	H 25
		SM2S (2 mtr Long)	H 65

2. HIGH FREQUENCY NEEDLE (MOTOR IN-HEAD NEEDLES)



IRFU / IEC (Valueline)

(In-Built High Frequency Needle, DIRECT PLUG IN)

Models as per Ø - IRFU30, IRFU38, IRFU45,

IRFU58, IRFU65

Hose Length: 5, 8*, 10 mtr.

Power Cable Length: 15 Mtr. cable

RPM: 12000

Input V.: 220 - 240 (Single Phase)

IREN / IE (Valueline)

(Requires an FREQUENCY CONVERTOR)

 $\textbf{Models as per } \textbf{\varnothing} \text{-} \text{IREN30, IREN38, IREN45,}$

IREN58, IREN65

Hose Length: 5 TO 16* mtr.

Power Cable Length: 15 Mtr. cable

RPM: 12000

Input V.: 42 volts



3. SHUTTER VIBRATOR (External Concrete Vibrator)



MODEL	AR 52	AR 26
RPM	Upto 6000	3000 - AR26/3/042 6000 - AR26/6/042
Centrifugal Force	8.22 to 14.23 kN	2.17 to 3.47 kN
Input V.	42 V	42 V
Best Used For	Bridges, Metro Piers, Segments, Girders, Precast Plants	Buildings, Woodens Formwork, Mivan Formwork
Clamp	Included	Bolting / Clamps (Extra)

4. FREQUENCY COVERTOR



MODEL	FUH 20	FUH 35	FUH 70/4	FUH 70/6	FUE M/S 75A FRP
INPUT / PHASE	SINGLE PHASE - 220 V			3 PHASE - 420 V	
OUTPUT			42 V		
OUTLET SOCKETS	1 (SINGLE)	2 (TWO)	4 (FOUR)	6 (SIX)	4 (FOUR)
CABLE			1.5 mtr		2.5 mtr
WEIGHT	8.9 Kgs.	18 Kgs.	28 Kgs.	38 Kgs.	26 Kgs.
INPUT / OUTPUT CURRENT (A)	7.8 / 20	9.5 / 35	16 / 58	16 / 58	13 / 75
MECHANICAL / ELECTRONIC	ELECTRONIC FREQUENCY CONVERTOR				
BEST SUITABLE FOR	HIGH FREQUENCY NEEDLES (IREN / IE) - (FUH70/6 - FOR AR26 Shutter Vibrator)				

MODEL	FUE - M/S 85A - FRP - SC		
INPUT / PHASE	3 PHASE - 420 V		
OUTPUT	42 V		
OUTLET SOCKETS	4 (FOUR) With RPM Controller & Individual Protection Switches		
CABLE	2.5 mtr		
WEIGHT	41 Kgs.		
INPUT / OUTPUT CURRENT (A)	13.7 / 85		
MECHANICAL / ELECTRONIC	ELECTRONIC FREQUENCY CONVERTOR		
BEST SUITABLE FOR	AR52 Shutter Vibrators with adjustable Freuquency & IREN / IE High Frequency Needles		



SOIL COMPACTION MACHINES





Wacker Neuson Tamping Rammer

MODEL	BS 60-2 Plus	DS-70
FUEL	PETROL	DIESEL
SELF WT.	66	83
Impact Force (kN)	18	21
Shoe Size (mm)	280x340	330x340

Wacker Neuson Walk Behind Roller


MODEL	RD7 Keh • Soil & Asphal	
FUEL	DIESEL	• 1.37 & 2.4 kN
ENGINE	KOHLER	 Electric Start
COMPACTION	2.4 kN	 Hydrostatic
DRUM SIZE (WXD)	650 X 400 (mm)	 Hour Meter
SELF WT.	784 kg.	 Automatic Brake
FUEL TANK (L)	5 LTRS.	 Long Draw Bar
WATER TANK (L)	60 LTRS.	 Made in India
HYD. OIL TANK	1.5 LTRS.	 Reverse Stop Safety feature



Wacker Neuson Make Plate Compactors

MODEL	MP 20	DPU 2550	DPU 3070	DPU 4545
MOVEMENT	FORWARD ONLY	REVERSIBLE	REVERSIBLE	REVERSIBLE
ENGINE BRAND & FUEL	HONDA - PETROL YANMAR - DIESEL	HATZ - DIESEL	HATZ - DIESEL	HATZ OR YANMAR DIESEL ENGINE
SELF WEIGHT (Kg.)	83 Kgs.	166 Kgs.	195 Kgs.	405 Kgs.
CENTRIFUGAL FORCE (kN)	20	25	30	45
PLATE SIZE (WIDTH) m.m.	500	500	700	600
PLATE THICKNESS (m.m)	10	10	10	12
START TYPE	ROPE START	ROPE START	ROPE START	SELF START
OTHER VARIANTS	MP 15 - 15 kN			

NOTES



OUR PRESTIGIOUS CLIENTELE









































Riddhi Construction - Surat Eagle Infra Ltd. - Mumbai

Shree Brahmani Construction Co. - Mehsana

Royal Infra - Surat

Jhajharia Nirman Ltd. - Bilaspur

A K Engg & Contractors - Jammu

DEC Infrastructure - Hyderabad

Capital Construction Pvt Ltd - Indore

Buildwell Engineers - Ankleshwar

Janak N Panchal (JNP Infra.) - Surat

Shripad Construction - Surat

Gopal Billcon - Surat

Decent Engineers - Surat

Akshar Constrcution Co - Unjha

3G Infra - Surat

Vijay M Mistry Construction - Surat H M Contractor - Navsari Niyati Engineering Pvt Ltd. - Surat Ramkumar Contractors Pvt Ltd - Panchkula

Ashray Infrastructure - Surat

Vimit Construction - Ankleshwar

Uday Infra - Dahej

Shreypath Infrastructure - Vadodara

LCC Projects Pvt Ltd - Surat

S.J. Contracts Pvt Ltd. - Pune

Rigid Construction - Surat

Konark Infra - Surat

Shree Mangalam Buildcon - Surat

Silicon Precast - Chikhli Kamar Infra - Thane

SMIT CORPORATION
An ISO 9001:2015 Certified Company
Manufacturer & Supplier of Construction Machinery

Regi. Address:

7/1165 B2, Asarawala Estate, B/H Hamd Park, Nr. Lalmiyan Masjid, Rampura, Surat, GJ. - 395001

Surat Office & Godown Address

59, Ganesh Industrial Society, Shantinath Mill Gali, Nr. Navjivan Circle, U.M. Road, Surat, GJ. - 395017

Mumbai Address

106, Appolo Arcade, Above HP Gas Service, Parsi Panchayat Road, Andheri (E), Mumbai, MH. - 400069

Ahmedabad Address

120, Shyam Industrial Park, Kujad-Bavda Road, Bakrol (Bujrang), Ahmedabad, GJ. - 382430



For Inquiry: +91-93275-56036 / +91-95120-71506 / +91-94085-22856 For Spares & Service Support: +91-95120-61506

ssmit.corporation@gmail.com / office.smitcorp@gmail.com / sales.smitcorp@gmail.com